

# **WESTEX ULTRASOFT® 3M TAPED FR WORK PANT Flame Resistant**

## **BP8000**

### **Features**

- Flame Resistant Westex UltraSoft® fabric
- 3M 8935 Reflective taped 'Hoop' pattern around legs
- Mobile phone pocket on right side
- 7 reinforced belt loops
- Single front pleats
- Twin back hip patch pockets
- 2 angled side pockets
- Coin pocket in waistband
- YKK branded zip front fly

#### **Fabric**

 Westex UltraSoft® Flame Resistant Fabric 88% Cotton/ 12% High Tenacity Nylon 237 gsm

### Size

Regular: 77-112Stout: 87-132



Navy **(BPCT)** 





Coin pocket along waistband seam

Waistband extension

Front slanted side pockets

YKK branded nylon zipper

6mm twin needle top stitching along back and front rise for extra strength

6mm twin needle top stitching along side for extra durability

3M branded retroreflective tape stitched all around leg in hoop pattern, finishing at side seam. 3M Scotchlite woven label attached on left leg















### **TECHNICAL FAQ's**

What is the in leg length on Regular (crotch to finish hem)?

77: 82cm, 82: 82cm, 87: 83cm, 92: 83cm,
97: 84cm, 102: 84cm, 107: 85cm, 112: 85cm

What is the in leg length on Stout (crotch to finish hem)?

87: 79cm, 92: 79cm, 97: 80cm, 102: 80cm,
107: 81cm,112: 81cm,117: 82cm, 122: 82cm,
127: 83cm,132: 83cm

What is the in leg length on Long (crotch to finish hem)?

• 74: 84cm, 79: 84cm, 84: 85cm, 89: 85cm, 94: 86cm

### **SIMILAR PRODUCTS**



**BP8010**WESTEX ULTRASOFT®
FR WORK PANT



**BP8090** TENCATE TECASAFE PLUS® FR PANT



**BP8090T**TENCATE TECASAFE PLUS®
TAPED FR PANT

### **AUSTRALIAN & INTERNATIONAL STANDARDS**

#### Australian/ New Zealand Standards

- **AS/NZS 2621:1998:** Textiles Guide to the Selection of Correct Care Labelling Instructions from AS/NZS 1957

  BISLEY WORKWEAR GARMENTS USE THE CORRECT CARE LABELLING SUITED TO THEIR TYPE AND FABRICATION
- AS/NZS 2392:1999: Textiles Labelling of Clothing, Household Textiles and Furnishings BISLEY WORKWEAR GARMENTS HAVE THE CORRECT CARE LABELLING PLACEMENT AND DETAILS
- AS/NZS 1957:1998: Textiles Care Labelling BISLEY WORKWEAR GARMENTS ARE PROVIDED WITH CARE INSTRUCTIONS SUITED TO THEIR TYPE AND FABRICATION
- **AS/NZS 2622:1996:** Textile Products Fibre Content Labelling BISLEY WORKWEAR GARMENTS ACCURATELY LIST THE FABRIC FIBRE CONTENT

- **AS/NZS 4399:1996:** Sun Protective Clothing Evaluation and Classification *THIS GARMENT HAS A SUN PROTECTION RATING OF UPF 50+ FOR ALL COLOURS*
- AS/NZS 1020:1995: The Control of Undesirable Static Electricity

  THIS GARMENT IS 100% COTTON WITH NO METAL ZIPS OR BUTTONS, THEREFORE IT MAY BE USED AS A STATIC CONTROL GARMENT
- **AS/NZS 1906.4:2010:** Hi Visibility Material For Safety Garments. RETROREFLECTIVE TAPE ON THIS GARMENT ALSO MEETS THE HIGHER RETROREFLECTIVE PERFORMANCE REQUIRED.

#### International Standards

• **ASTM D5489-07:** Standard Guide for Care Symbols for Care Instructions on Textile Products

\*\*BISLEY WORKWEAR GARMENTS COMPLY\*\*

- WITH USA STANDARDS FOR CARE LABEL SYMBOLS AND CONTENT DESCRIPTIONS
- **ISO 14184-1:** Textiles Determination of Formaldehyde Part 1: Free and Hydrolized Formaldeyhe (Water Extraction Method) BISLEY WORKWEAR GARMENTS ARE FREE FROM FORMALDEHYDE
- EN 340, 1149-3 & 13034
- EN/ISO 11612 & 11611
- REACH Certified
- NFPA 70E, 2112, 1977
- OSH 1910.269
- IEC/ ISO 61482-2 (CLASS 1)
- ISO 14184-1
- ASTM F1506, F1002, F1959/F1959M-06ae1
- ISO 14184
- OEKO-TEX 100 (CLASS II)

PANTS												MENS
Size REGULAR	77R	82R	87R	92R	97R	102R	107R	112R				
To fit waist size (cm)	77	82	87	92	97	102	107	112				
To fit waist size (inches)	30	32	34	36	38	40	42	44				
In-leg length (cm)	80	82	84	84	85	85	86	86				
Size STOUT			<i>87S</i>	<i>928</i>	<i>978</i>	102S	107S	112S	117S	122S	127S	132S
To fit waist size (cm)			87	92	97	102	107	112	117	122	127	132
To fit waist size (inches)			34	36	38	40	42	44	46	48	50	52
In-leg length (cm)			78	80	80	82	82	84	84	84	84	84
Size LONG	74L	79L	84L	89L	94L							
To fit waist size (cm)	74	79	84	89	94							
To fit waist size (inches)	29	31	33	35	37							
In-leg length (cm)	85	85	87	87	88							